

## Construction

## ALUMINIUM LOADING RAMPS for wheeled and rubber tracked vehicles



### TECHNICAL DETAILS

Side edges	2
Maximum load capacity	550 kg
Length	from 1,5 to 3,0 m
Width	200 mm

### LIGHT LOADS

MODEL	LOAD CAPACITY FOR VEHICLES WITH WHEELBASE			TOTAL LENGTH	WIDTH		WEIGHT PER RAMP
	1,0 m	1,5 m	2,0 m		INTERNAL	EXTERNAL	
	kg				mm	mm	
50-18/10	300	-	-	1800/1000	150	200	6,5
50-24/14	240	-	-	2400/1400	150	200	8,5
50-30/18	200	-	-	3000/1800	150	200	10,5
50.15	550	-	-	1.500	150	200	5
50.20	400	-	-	2.000	150	200	6,5
50.25	300	-	-	2.500	150	200	8
50.30	280	-	-	3.000	150	200	9,5

## Construction

## ALUMINIUM LOADING RAMPS for wheeled and rubber tracked vehicles



### TECHNICAL DETAILS

Side edges	2 or none
Maximum load capacity	14.000 kg
Length	from 1,5 to 5,0 m
Width	from 310 to 640 mm

### LIGHT LOADS

TYPE	LOAD CAPACITY FOR VEHICLES WITH WHEELBASE			TOTAL LENGTH	WIDTH		WEIGHT PER RAMP
	1,0 m	1,5 m	2,0 m		INTERNAL	EXTERNAL	
	kg				mm	mm	
55.15	1.650	1.850	1.850	1.500	-	310	8
55.20	1.200	1.350	1.350	2.000	-	310	10,5
55.25	900	1.000	1.140	2.500	-	310	13
55.30	700	800	935	3.000	-	310	15,5
55.35	550	650	795	3.500	-	310	18
65.20	1.595	2.150	2.250	2.000	-	345	12
65.25	1.290	1.400	1.750	2.500	-	345	14
65.30	1.085	1.100	1.350	3.000	-	345	17
65.35	750	935	1.000	3.500	-	345	20
85.20	3.200	3.200	3.200	2.000	-	300	14
85.25	2.300	2.500	2.500	2.500	-	300	16
85.30	1.770	2.000	2.000	3.000	-	300	19
85.35	1.400	1.600	1.700	3.500	-	300	21
85.40	1.200	1.330	1.480	4.000	-	300	24

# Construction

## MEDIUM LOADS

MODEL	LOAD CAPACITY FOR VEHICLES WITH WHEELBASE			TOTAL LENGTH	WIDTH		WEIGHT PER RAMP
	1,0 m	1,5 m	2,0 m		INTERNAL	EXTERNAL	
	kg				mm	mm	
100.25	2650	2.850	2.850	2.500	300	360	18
100.30	2000	2.300	2.300	3.000	300	360	21
100.35	1.600	1.800	1.970	3.500	300	360	24
100.40	1.300	1.500	1.700	4.000	300	360	27
115.25	3.400	3.680	3.680	2.500	300	360	19
115.30	2.600	3.000	3.000	3.000	300	360	23
115.35	2.100	2.370	2.500	3.500	300	360	27
115.40	1.750	1.950	2.170	4.000	300	360	31
115.45	1.500	1.650	1.800	4.500	300	360	35
125.25	5.000	5.400	5.400	2.500	350	410	25
125.30	3.300	4.500	4.500	3.000	350	410	30
125.35	3.000	3.500	3.560	3.500	350	410	35
125.40	2.500	2.900	3.070	4.000	350	410	40
125.45	2.000	2.450	2.570	4.500	350	410	45
125.50	1.880	2.035	2.205	5.000	350	410	50
140.25	5.888	6.251	6.251	2.500	400	460	28
140.30	4.429	5.049	5.049	3.000	400	460	33
140.35	3.544	4.013	4.234	3.500	400	460	38
140.40	2.952	3.278	3.646	4.000	400	460	44
140.45	2.529	2.769	3.044	4.500	400	460	49
140.50	2.212	2.395	2.602	5.000	400	460	54
155.25	6.930	7.420	7.420	2.500	350	410	29
155.30	5.250	6.020	6.020	3.000	350	410	34
155.35	4.220	4.770	5.060	3.500	350	410	40
155.40	3.530	3.910	4.360	4.000	350	410	45
155.45	3.030	3.310	3.640	4.500	350	410	50
155.50	2.650	2.870	3.120	5.000	350	410	55
165.25	8.560	9.170	9.170	2.500	400	460	35
165.30	6.490	7.440	7.440	3.000	400	460	41
165.35	5.220	5.900	6.260	3.500	400	460	47
165.40	4.360	4.840	5.390	4.000	400	460	51
165.45	3.750	4.090	4.500	4.500	400	460	57
165.50	3.280	3.550	3.850	5.000	400	460	63

# Construction

## LARGE VERSION

MODEL	LOAD CAPACITY FOR VEHICLES WITH WHEELBASE			TOTAL LENGTH	WIDTH		WEIGHT PER RAMP
	1,0 m	1,5 m	2,0 m		INTERNAL	EXTERNAL	
	kg				mm	mm	
155.25 L	6.930	7.420	7.420	2.500	400	460	31
155.30 L	5.250	6.020	6.020	3.000	400	460	37
155.35 L	4.220	4.770	5.060	3.500	400	460	43
155.40 L	3.530	3.910	4.360	4.000	400	460	48
155.45 L	3.030	3.310	3.640	4.500	400	460	54
155.50 L	2.650	2.870	3.120	5.000	400	460	60
165.25 L	8.560	9.170	9.170	2.500	450	510	35
165.30 L	6.490	7.440	7.440	3.000	450	510	41
165.35 L	5.220	5.900	6.260	3.500	450	510	48
165.40 L	4.360	4.840	5.390	4.000	450	510	54
165.45 L	3.750	4.090	4.500	4.500	450	510	60
165.50 L	3.280	3.550	3.850	5.000	450	510	67

## HEAVY LOADS

MODEL	LOAD CAPACITY FOR VEHICLES WITH WHEELBASE			TOTAL LENGTH	WIDTH		WEIGHT PER RAMP
	1,0 m	1,5 m	2,0 m		INTERNAL	EXTERNAL	
	kg				mm	mm	
170.25	10.000	10.000	10.000	2.500	450	510	39
170.30	7.300	8.300	8.400	3.000	450	510	41
170.35	5.700	6.600	7.200	3.500	450	510	47
170.40	5.000	5.600	6.200	4.000	450	510	54
170.45	4.300	4.700	5.100	4.500	450	510	67
170.50	3.700	4.000	4.300	5.000	450	510	72
180.25	11.466	12.173	12.173	2.500	450	510	40
180.30	8.624	9.832	9.832	3.000	450	510	46
180.35	6.902	7.815	8.246	3.500	450	510	53
180.40	5.749	6.384	7.101	4.000	450	510	60
180.45	4.325	5.392	5.928	4.500	450	510	68
180.50	4.307	4.664	5.067	5.000	450	510	74
190.25	14.000	14.000	14.000	2.500	500	580	51
190.30	10.800	12.300	12.300	3.000	500	580	61
190.35	8.600	9.800	10.300	3.500	500	580	70
190.40	7.200	8.000	8.800	4.000	500	580	80
190.45	6.100	6.700	7.400	4.500	500	580	89
190.50	5.300	5.800	6.300	5.000	500	580	99
210.30	14.000	14.000	14.000	3.000	550	640	69
210.35	11.900	13.500	14.000	3.500	550	640	79
210.40	9.800	10.900	12.100	4.000	550	640	90
210.45	8.400	9.200	10.100	4.500	550	640	101
210.50	7.300	7.900	8.600	5.000	550	640	112