



Performance and productivity

- Best load capacities
- Rear axle lock and tilt corrector in standard
- Flow Sharing in standard enabling a simultaneous and proportional control of 4 movements

Powerful and robust

- High strength monoblock chassis
- Rough terrain capacities
- Hydrostatic transmission and inching pedal

Comfort and ergonomomy

- Driving position reducing fatigue at work
- Load Moment Indicator (LMI) easy to read including automatic cut off dangerous movements
- High safety cab
- Smart control 4 in 1 Joystick



HTL 5210



TELEHANDLER



PERFORMANCES

Maximum lift capacity	5200 kg
Lift capacity to full height	5200 kg
Lift capacity at full reach	3500 kg
Maximum fork height	10 m
Reach at maximum fork height	0.3 m
Maximum forward reach	5.7 m



DIMENSIONS

A Length	6.28 m
B Width	2.43 m
C Height	2.6 m
D Wheelbase	2.89 m
E Ground clearance	50 cm
F Track width	2 m
G Cab width	0.96 m
H Overall width - stabilizers down	3.34 m
I Height to high boom pivot	1.75 m
J Approach angle	29 °
K Upper rotation of forks	18 °
L Lower rotation of forks	122 °
Turning radius (outside wheels)	4,5
Weight with forks	10810 kg
Tyres type	400/80-24



ENGINE

Engine model	PERKINS TIER III	PERKINS TIER IV
Engine Capacity	4400 cm3	3400 cm3
Engine power output	70kW @ 2300rpm	83kW @ 2200rpm
Engine torque	392Nm @ 1400rpm	450Nm @ 1400rpm
Transmission type	Hydrostatic	
Fuel tank	130 l	130 l
Engine oil	7 l	9.5 l

STANDARD EQUIPMENT

- Backlighted e-tronic dashboard
- Hydrostatic transmission
- 4 wheels drive and steer
- Simultaneous and proportional controls for boom / telescopic arm / excavation and accessories movements
- Safety valves on hydraulic jacks
- Auxiliary hydraulic system
- Cut-off of dangerous movements when overloaded
- Tilt corrector: +/- 10°
- ROPS/FOPS cabin with heating and ventilation
- Hydraulic rear axle locking

OPTIONS AND ACCESSORIES

- Winches
- Jibs
- Forks
- Buckets
- Air conditioning
- Working lights
- Metal windscreen protector (FOPS)
- Rear camera
- Reverse fan

