




# LB30


## LowBoy





Motore Perkins 1104D-44 – 4 cilindri –  
USA EPA Tier 3/EU STAGE IIIA –  
Potenza massima kW/Hp 74,5/100  
@2300 RPM – Trasmissione idrostatica  
– Resa [m<sup>3</sup>] 2,8 (Slump ≤ 40 mm) –  
Inching di serie – Mix control e comandi  
da terra di serie. 

Perkins Engine 1104D-44 – 4 cylinders   
– USA EPA Tier 3/EU STAGE IIIA –  
Maximum rated power kW/Hp 74,5/100  
@ 2300 RPM – Hydrostatic driveline –  
Net Output - [m<sup>3</sup>] 2,8 (Slump ≤ 40 mm)  
– Inching system – Mix control and  
ground controls.

Moteur Perkins 1104D-44 – 4 cylindres   
– USA EPA Tier 3/EU STAGE IIIA –  
Puissance max kW/Hp 74,5/100 @2300  
RPM – Transmission hydrostatique –  
Rendement [m<sup>3</sup>] 2,8 (Slump ≤ 40 mm)  
– Inching de série – Mix control et  
commande du sol de série.

Motor Perkins 1104D-44 – 4 cilindros   
– USA EPA Tier 3/EU STAGE IIIA –  
Potencia máxima kW/Hp 74,5/100 @  
2300 RPM – Transmisión hidrostática  
– Rendimiento - [m<sup>3</sup>] 2,8 (Slump ≤ 40  
mm) – Sistema Inching – Mix control  
y comandos desde el suelo.

Motor Perkins 1104D-44 – 4 cilindros   
– USA EPA Tier 3/EU STAGE IIIA –  
Máxima potência avaliada kW/Hp  
74,5/100 @ 2300RPM – Transmissão  
Hidrostatica – Rendimento Real - [m<sup>3</sup>]  
2,8 (Slump ≤ 40 mm) – Sistema Inching  
– Mix control e controles do solo.


Дизельный Perkins 1104D-44 – 4-х   
цилиндры – Соответствующий  
нормам USA EPA Tier 3/EU STAGE IIIA  
– Максимальная мощность 74,5/100 kW/  
лс при 2300 об/мин – Гидростатическая  
трансмиссия– Выход бетона 2,8 м<sup>3</sup>  
(Испытание бетона резкий спад: ≤  
40мм) – Управление барабана и системы  
водоснабжения с земли. Инчинг педаль.





# LB30


## LowBoy





Motore Perkins 1104D-44 – 4 cilindri –  
USA EPA Tier 3/EU STAGE IIIA –  
Potenza massima kW/Hp 74,5/100  
@2300 RPM – Trasmissione idrostatica  
– Resa [m<sup>3</sup>] 2,8 (Slump ≤ 40 mm) –  
Inching di serie – Mix control e comandi  
da terra di serie. 

Perkins Engine 1104D-44 – 4 cylinders   
– USA EPA Tier 3/EU STAGE IIIA –  
Maximum rated power kW/Hp 74,5/100  
@ 2300 RPM – Hydrostatic driveline –  
Net Output - [m<sup>3</sup>] 2,8 (Slump ≤ 40 mm)  
– Inching system – Mix control and  
ground controls.

Moteur Perkins 1104D-44 – 4 cylindres   
– USA EPA Tier 3/EU STAGE IIIA –  
Puissance max kW/Hp 74,5/100 @2300  
RPM – Transmission hydrostatique –  
Rendement [m<sup>3</sup>] 2,8 (Slump ≤ 40 mm)  
– Inching de série – Mix control et  
commande du sol de série.

Motor Perkins 1104D-44 – 4 cilindros   
– USA EPA Tier 3/EU STAGE IIIA –  
Potencia máxima kW/Hp 74,5/100 @  
2300 RPM – Transmisión hidrostática  
– Rendimiento - [m<sup>3</sup>] 2,8 (Slump ≤ 40  
mm) – Sistema Inching – Mix control  
y comandos desde el suelo.

Motor Perkins 1104D-44 – 4 cilindros   
– USA EPA Tier 3/EU STAGE IIIA –  
Máxima potência avaliada kW/Hp  
74,5/100 @ 2300RPM – Transmissão  
Hidrostatica – Rendimento Real - [m<sup>3</sup>]  
2,8 (Slump ≤ 40 mm) – Sistema Inching  
– Mix control e controles do solo.

Дизельный Perkins 1104D-44 – 4-х   
цилиндры – Соответствующий  
нормам USA EPA Tier 3/EU STAGE IIIA  
– Максимальная мощность 74,5/100 kW/  
лс при 2300 об/мин – Гидростатическая  
трансмиссия – Выход бетона 2,8 м<sup>3</sup>  
(Испытание бетона резкий спад: ≤  
40мм) – Управление барабана и системы  
водоснабжения с земли. Инчинг педаль.

